

FLOCON EDGE MAINTENANCE UNIT OFF ROAD SUIT HOTMIX & PREMIX

Flocon Model Number	EMU1R5	EMU1R6	EMU1R7	EMU1R8	EMU1R10LZY	EMU1RTD12	EMU1RTD15
Patching Mix Hopper Capacity (m ³)	3.5	4	4.6	5	7	8	11
Body Conveyor Type	Chain	Chain	Chain	Chain	Chain	Chain	Chain
Tack Coat Material Volume (Litres) (Emulsion or Light Grade Cutback)	220	270	320	320-1000	500-1500	500-1500	500-2000
Kerosene Tank Volume (Litres)	40	40	40	60	60	60	60
Water Tank Volume (Litres)	100	120	150	150	200	200	200
Hydraulic Oil Volume (Litres)	60	60	60	60	60	60	60
Approximate Tare Weight (Kg)	1800	1900	2000	2100	2300	2400	2800
Approximate Legal Payload (Kg)	4000	5000	6000	7000	11000	12500	14500

Cab Chassis Requirements

Axles	4 x 2	4 x 2	4 x 2	4 x 2	6 x 2	6 x 4	8 x 4
Preferred cab to axle (mm)	3200	3200	3200	3200	3200 - 3800	3200 - 3800	4800
Approximate vehicle GVM (kg)	10000	12000	14000	16000	22500	22500	26500
Transmission							

Shipping Details

Length (mm)	4500	4500	4500	4500	4800	5200	7000
Overall Width (mm)	2400	2400	2400	2400	2400	2400	2400
Height (body only) (mm)	1600	1700	1800	1900	1900	2000	2200

The following is included in the above models unless otherwise specified:

Shovel bin, spreader plate, side chute and shovel cleaning bin

Insulation, body heating including heat isolation valve

Hydraulic operated compacting equipment carrier

Insulated tarpaulin

Emulsion system including open impeller pump, tank & hose reel

Water tank with wash tap only

Emulsion flushing system

Small locker on kerb side

Open tray on drivers side, large locker on Models 10 and 15

Manual operated patrol sign with amber rotating lights

500 mm off road edge maintenance unit and hydraulic winching system

Hydraulics, electrics, painting and installation included

Options refer to buyer check list