

FLOCON AGGREGATE & SEALING UNIT SUIT EMULSION & GRIT

Flocon Model Number	ASUEG5	ASUEG6	ASUEG7	ASUEG8	ASUEG10LZY	ASUEGTD12	ASUEGTD15
Patching Mix Hopper Capacity (m ³)	3.5	4	4.6	5	7	8	11
Body Conveyor Type Chain Drive (CC) / Rubber Drive (RB)	CC or RB	CC or RB	CC or RB	CC or RB	CC or RB	CC or RB	CC or RB
Tack Coat Material Volume (Litres) (Emulsion or Light Grade Cutback)	500	600	700	1000	1200	1500	2000
Kerosene Tank Volume (Litres)	40	40	40	60	60	60	60
Water Tank Volume (Litres)	100	120	150	150	200	200	200
Hydraulic Oil Volume (Litres)	60	60	60	60	60	60	60
Approximate Tare Weight (Kg)	1800	1900	2000	2100	2300	2400	2800
Approximate Legal Payload (Kg)	4000	5000	6000	7000	11000	12500	14500
Cab Chassis Requirements							
Axles	4 x 2	4 x 2	4 x 2	4 x 2	6 x 2	6 x 4	8 x 4
Preferred cab to axle (mm)	3200	3200	3200	3200	3200 - 3800	3200 - 3800	4800
Approximate vehicle GVM (kg)	10000	12000	14000	16000	22500	22500	26500
Transmission							
Shipping Details							
Length (mm)	4500	4500	4500	4500	4800	5200	7000
Overall Width (mm)	2400	2400	2400	2400	2400	2400	2400
Height (body only) (mm)	1600	1700	1800	1900	1900	2000	2200
PRICE AUD GST EXCLUSIVE	\$	\$	\$	\$	\$	\$	

The following is included in the above models unless otherwise specified:

Shovel bin, spreader plate, side chute and shovel cleaning bin
 Insulation, body heating including heat isolation valve if required
 Hydraulic operated compacting equipment carrier
 Insulated tarpaulin
 Emulsion system including open impeller pump, tank and hose-reel

Small locker on kerb side
 Open tray on drivers side, large locker on Models 10 and 15
 Manual operated patrol sign with amber rotating lights
 2400 mm four door aggregate spreader with hydraulic driven augers
 2400 mm spray bar with nozzle isolation

Water tank with wash tap only
Emulsion flushing system

Hydraulics, electrics, painting and installation included
Options refer to buyer check list