

# FLOCON FLOPATCHER

Flocon Model Number	MINI PATCHER	HDRBFP5	HDRBFP6	HDRBFP7	HDRBFP8	HDRBFP10LZY	HDRBFPTD12	HDRBFPTD15
Patching Mix Hopper Capacity (m <sup>3</sup> )	1.5	3.5	4	4.6	5	7	8	11
Tack Coat Material Volume (Litres) (Emulsion or Light Grade Cutback)	205 drum	220	270	320-1000	320-1000	500-1500	500-1500	500-2000
Kerosene Tank Volume (Litres)	20	40	40	40	60	60	60	60
Water Tank Volume (Litres)	60	100	120	150	150	200	200	200
Hydraulic Oil Volume (Litres)	40	60	60	60	60	60	60	60
Approximate Tare Weight (Kg)	1500	1800	1900	2000	2100	2300	2400	2800
Approximate Legal Payload (Kg)	N/A	4000	5000	6000	7000	11000	12500	14500
<b>Cab Chassis Requirements</b>								
Axles	N/A	4 x 2	4 x 2	4 x 2	4 x 2	6 x 2	6 x 4	8 x 4
Preferred cab to axle (mm)	N/A	3200 -3800	3200 -3800	3200 -3800	3200 -3800	3200 - 3800	3200 - 3800	4800
Approximate vehicle GVM (kg)	N/A	10000	12000	14000	16000	22500	22500	26500
Transmission	N/A	Auto or Manual gearbox with PTO or Live Drive (Live drive outlet must be supplied on the cab chassis)						
<b>Shipping Details</b>								
Length (mm)	2500	4500	4500	4500	4500	4800	5200	7000
Overall Width (mm)	1500	2400	2400	2400	2400	2400	2400	2400
Height (body only) (mm)	1500	1600	1700	1800	1900	2000	2000	2200

The Mini-Patcher is a self contained basic skid mounted blower technology unit designed to be carried on a trailer / tipper or flat rack type body.  
(Trailer GVM approx 4500 kg or Truck GVM approx 6500 kg)

**The following is included in models HDRBFP5 through to HDRBFPTD15:**

Rubber belt type conveyor  
 Hydraulic operated compacting equipment carrier  
 Insulated tarpaulin  
 Emulsion system including open impeller pump, tank and hose-reel  
 Water tank with wash tap only  
 Emulsion flushing system

Small locker on kerb side  
 Open tray on drivers side, large locker on Models 10 and 15  
 Manual operated patrol sign with amber rotating lights  
 Hydraulics, electrics, painting and installation included  
**Options refer to buyer check list**