

FLOCON STABILISATION UNIT

Flocon Model Number	HDRBVN8	HDRBVN12	HDRBVN16	HDRBVN21	HDRBVN24
Capacities					
Hopper Capacity (m ³)	6.2	8.2	16	21	24
Body Conveyor Type	Rubber Belt	Rubber Belt	Rubber Belt	Rubber Belt	Rubber Belt
Hydraulic Oil Volume (Litres)	100	100	100	100	100
Cab Chassis Requirements					
Axles	4 x 2	6 x 4	8 x 4	8 x 4	8 x 4
Preferred cab to axle (mm)	3200	3200	4800	4800	4800
Approximate vehicle GVM (kg)	16000	22500	26500	26500	26500
Transmission	Manual type gearbox with PTO or Engine live drive acceptable				
Shipping Details					
Length (mm)	4800	5200	7000	7000	7000
Overall Width (mm)	2400	2400	2400	2400	2400
Height (body only) (mm)	1600	2200	2400	2600	2800
Weight (kg)	2500	2800	3200	3400	3600
Options Available:					
Weighing system with digital read out and docket printer			Automatic cleaning internally drained tanker filling breather system		
The above includes the following:					
Rubber belt type conveyor			Left and right hand lockers		
Transmission PTO and Pump or live drive pump only			Fan forced DC electric oil cooler		
Hydraulics, electrics, installation and painting			2400 mm Hydraulic driven 8" Vane (5 to 20 kg/m ²) or 10" Vane (10 to 30 kg/m ²)		
Two or four external tanker filling breather bags			Fully sealed body with 2 plant filling hatches & one tanker filling point		
Front and rear amber beacons, plastic truck mate guards			Electronic and manual spreading control system		